

A measure of individual role in collective dynamics: spreading at criticality

Konstantin Klemm,¹ M. Ángeles Serrano,² Víctor M. Eguíluz,³ and Maxi San Miguel³

¹Department of Bioinformatics, Leipzig University, Härtelstrasse 16-18, 04107 Leipzig, Germany

²Departament de Química Física, Universitat de Barcelona, Martí i Franquès 1, 08028 Barcelona, Spain

³Instituto de Física Interdisciplinar y Sistemas Complejos IFISC (CSIC-UIB),
Campus Universitat Illes Balears, E07122 Palma de Mallorca, Spain

Identifying key players in collective dynamics remains a challenge affecting a great variety of research fields, from the efficient dissemination of ideas to drug target discovery in biomedical problems. The difficulty lies at several levels: how to single out the role of individual elements in such intermingled systems, or which is the best way to quantify their importance. Centrality measures aim at capturing the influence of a node from its position in a network. The key issue obviated is that the contribution of a node to the collective behavior is not uniquely determined by the structure of the system but it is a result of the interplay between dynamics and network structure. Here we show that *dynamical influence* measures explicitly how strongly a node's dynamical state affects collective behavior. For diffusive processes in complex networks, dynamical influence quantifies how efficiently real systems may be driven by manipulating the state of single nodes. For critical spreading, it targets nodes with superior spreading capabilities.

Complex networks are a groundbreaking concept that is helping to understand the behaviour of many chemical, biological, social and technical systems [1, 2]. Network representations are particularly suitable for systems where heterogeneity dominates and is crucial for dynamics [3], where a few nodes are usually considered as the most important. Oftentimes, node importance is correlated with centrality measures, local [4, 5] or global [6], which are generally based on a purely topological perspective and do not explicitly account for the dynamics. However, dynamics is fundamental in assessing the impact of individual elements in global performance. Here, we show that *dynamical influence* is a centrality measure able to quantify how strongly a node's dynamical state affects the collective behavior of a system, taking explicitly into account the interplay between structure and dynamics in complex networks. We prove that it applies equally well to a variety of families of dynamical models, from spreading phenomena at the critical point, for which dynamical influence targets nodes with superior spreading capabilities, to diffusive processes, for which it quantifies how efficiently real systems may be driven by manipulating the state of single nodes.

Classical centrality measures in complex networks – like the degree or number of neighbors a node interacts with [4, 5], betweenness centrality [7] counting the number of shortest paths through a certain node, eigenvector centrality [8] based on the idea that relations with more influential neighbors confer greater importance, or the k -shell decomposition [9] that correlates with the outcome of supercritical spreading originating in specific nodes [10]– rely only on topology, even if an underlying process can be indirectly associated in some cases. In contrast, the impact of individual elements in the global performance of the system inevitably depends on the specificities of the dynamics. Targeting individuals for vaccination strategies in epidemic processes is not the same as selecting electrical stimulation sites in the brain in

order to suppress epileptic seizures. In this respect, a Laplacian-based centrality measure [11–13], closely related to PageRank [14], has been proposed recently to assess the importance of complex network nodes in specific dynamical models.

In this work, we provide a remarkably general and rigorous framework where dynamical influence is defined as a centrality measure both on directed and on undirected complex networks and applies to a variety of families of dynamical models, including epidemic spreading models like the susceptible-infected-removed (SIR), the susceptible-infected-susceptible (SIS), and the contact process, and diffusive processes like the voter model or phase coupled oscillators. In all cases, dynamical influence is calculated as the left eigenvector associated to the largest eigenvalue zero of a characteristic matrix of the system, that encodes the interplay between topology and dynamics.

More specifically, we focus on systems of N time-dependent real variables $x = (x_1, \dots, x_N)$ with coupled linear dynamics specified by a $N \times N$ real matrix M

$$\dot{x} = Mx. \quad (1)$$

A first classification of the dynamics is obtained by considering the largest eigenvalue μ_{max} of M . For $\mu_{max} < 0$, $x(t)$ converges to a null vector that represents a stable fixed point solution; for $\mu_{max} > 0$, indefinite growth from almost all initial conditions is observed. Suppose that M is such that a non-degenerate $\mu_{max} = 0$ exists. Then, the scalar product $\phi_c = c \cdot x$ is a conserved quantity, where c is the left eigenvector of M for μ_{max} ,

$$\frac{d\phi_c}{dt} = c \cdot \dot{x}(t) = [cM] \cdot x(t) = 0. \quad (2)$$

The existence of the conserved quantity allows to calculate the final state in terms of the initial condition $x(0)$ as

$$x(\infty) := \lim_{t \rightarrow \infty} x(t) = \frac{c \cdot x(0)}{c \cdot e}, \quad (3)$$

where e is a right eigenvector of M for μ_{max} . Eq. (1) implies that the projection of $x(0)$ on c is all the system remembers at large times about the initial condition $x(0)$. Therefore, we call c_i the *dynamical influence* of element i in the dynamics under Eq. (1). It is easily calculated without expensive numerical simulations.

Let us first apply these insights to critical phenomena like spreading processes [15]. In the SIR model [16], each node is either susceptible, infected or removed. An infected node i transfers the epidemic along each of its outgoing arcs independently with probability β ; node i itself relaxes to the removed state at unit rate. As the *spreading efficiency* (details in Methods) of node i we define the expected fraction of nodes reached by an epidemic outbreak initiated with a node i infected, all others susceptible. We call i the *seed node*. Viewing such a configuration as a small perturbation to the stationary state with all nodes susceptible, we approximate the dynamics by the linearization

$$\dot{x} = -x + \beta A^T x. \quad (4)$$

Here $x_j(t)$ is the probability of node j to be infected at time t . The first term is the relaxation from the infected to the removed state at unit rate. The second term quantifies the transmission of the epidemic where the network enters by the transpose of its adjacency matrix A .

Equation (4) can be rewritten as Eq. (1) with $M = \beta A^T - I$ and I the identity matrix. Matrix M has largest eigenvalue $\mu_{max} = 0$ when the spreading probability β is the inverse of the largest eigenvalue of A , that is $\beta = \beta_c = 1/\alpha_{max}$. We take again c as a left eigenvector of M at $\mu_{max} = 0$ or, equivalently, a right eigenvector of A at its maximum eigenvalue α_{max} . Then the effect of an initial infection described by the probability vector $x(0)$ is proportional to $c \cdot x(0)$.

Now we ask how well c may forecast the actual SIR spreading dynamics. Figure 1 shows that c_i is a good predictor of spreading efficiency at critical parameter value $\beta = \beta_c$ in a small social network. Dynamical influence c_i outperforms the predictions made by degree, shell index and betweenness centrality. Predictive power is quantified by the rank order correlation (see Methods).

Figure 2 shows the predictive power of dynamical influence for spreading efficiency as a function of the infection probability in larger real-world networks and the Barabasi-Albert model. The results are as anticipated by the theory. Dynamical influence is a good predictor of spreading efficiency in the critical regime where $\beta/\beta_c \approx 1$. In this regime predictions by dynamical influence outperform those by other quantities that are supposed to provide information about expected outbreak size.

For sub- and supercritical parameter values β , however, the degree d_i of a node i is a good predictor of




FIG. 1: Spreading efficiency compared to centrality measures in a social network. The network of Zachary's karate club [17] has 77 edges connecting 34 nodes, here ordered according to decreasing spreading efficiency. A monotonic decay of a centrality measure in the diagram indicates large predictive power for spreading efficiency. The rank order correlation of spreading efficiency is of 0.97 with dynamical influence, 0.86 with degree, 0.82 with shell index, and 0.79 with betweenness centrality. Indexing of nodes is the same as in [17]. In the network drawing, circles and squares represent the primary partitioning of the node set found by Girvan and Newman [18]. Spreading efficiency has been estimated at $\beta = \beta_c = 0.15$ performing 10^6 independent runs of the SIR model per seed node. The largest eigenvalue of the network adjacency matrix is 6.65.

spreading efficiency. In the subcritical regime, spreading is sparse and typically confined to the neighborhood of the seed node i , while in the supercritical regime, the epidemics rarely fails to spread to the whole system. In the critical regime in-between these extremes, infectious seeds are perturbations that trigger relaxation dynamics at all scales. This is reflected in a dynamics dominated by a marginal linear mode and a variety of possible final states. Dynamical predictions require then a global




FIG. 2: Predictive power for spreading efficiency as a function of the spreading parameter β for the SIR model. Symbols are values of the rank order correlation coefficient of spreading efficiency with influence (squares), degree (triangles) and shell index (circles). Vertical dashed lines indicate the critical value β_c . The predictive power of betweenness centrality (not shown) is below that of degree in all cases. The following networks have been used. E-mail interchanges between employees of a university [19]; unweighted neural circuitry of the roundworm *C. elegans* [20, 21]; snapshot of the Internet at Autonomous Systems level of Nov 08, 1997, see <http://moat.nlanr.net>; a realization of the Barabási-Albert (BA) model of scale-free networks [4] with 1000 nodes and $m = 2$ edges added per node. Other realizations of the BA model yield qualitatively the same result. For the BA model, shell index is not a predictor because its value $k_i = m$ is the same for all nodes. For the neural network, being directed, out-degree instead of degree is used as a predictor and for calculating the shell index.

view of the network structure and the final state is determined by the conservation law associated with the leading eigenvector c . The predictive power does not have its maximum at the linear prediction $\beta/\beta_c \approx 1$ possibly due to the fact the infection cannot return to the node from which it has come [22].

Repeating the numerical experiments with the SIS model (see Methods) on the same networks, we obtain results (not shown) qualitatively similar to those of Figure 2. Prediction by dynamical influence may also be applied to the contact process [23]. A is replaced by the stochastic adjacency matrix, the adjacency matrix after normalization such that each row sums up to 1.

Coming back to the general framework Eq. 1, there is a class of dynamical processes in networks in which the property of M having a zero maximum eigenvalue appears naturally without the need of adjusting any pa-




FIG. 3: **Node dynamical influence and driving in a system of phase-coupled oscillators.** **a**, Adaptation of the *global* phase of the four-node system in the inset when driving is applied to one of the oscillator nodes (an additional oscillator (not shown) coupled to the red circle node with fixed phase $\pi/2$). Adaptation is quick when driving at nodes 1 ($\circ$) and 4 (Δ), having high influence, and slow when driving at one of the other two nodes, having low influence. **b**, Driving efficiency (filled diamonds) and dynamical influence (shaded squares) for a system of phase oscillators coupled as the network of regions in the macaque cortex [24]. Driving efficiency of node i is measured as the time required to resynchronize with an additional input signal applied to a given node i . We say that the system has resynchronized when the global phase reaches $\psi(t) \geq (1 - \epsilon)x_a$ with a tolerance $\epsilon = 10^{-2}$, where the global phase $\psi(t)$ is computed as the argument of the global order parameter $z(t) = r \exp[i\psi(t)] = \sum_{i=1}^N \exp[i\psi_i(t)]$. For comparison, the degree ratio $k_{\text{out}}/k_{\text{in}}$ of each node is also shown (open triangles). Since this is not an uncorrelated network, node influence deviates significantly from degree ratio.

rameter. This is the case of diffusive processes defined by Eq. 1 with $M = -L$ and the Laplacian matrix entries

$$L_{ij} = -K_{ij} + \delta_{ij} \sum_{k=1}^N K_{ik}. \quad (5)$$

The zero eigenvalue of L is non-degenerate under mild assumptions [25]. For these processes our general analysis of Eq. 1 becomes exact. A prominent example of diffusive dynamics is the voter model [26] in which node i is in a spin state $s_i \in \{-1, +1\}$. For this model, x_i stands for

the ensemble average of spin i , $x_i = \langle s_i \rangle$, and K_{ij} gives the rate at which node i copies the state of node j . Different definitions of the voter model dynamics provide clear examples of how the concept of dynamical influence takes into account the interplay between topology and dynamics: For *link update* dynamics in an undirected network, an ordered pair of nodes (i, j) is chosen in each step and node i copies the state of node j . The rate matrix K becomes then the adjacency matrix A . As a consequence $c_i = 1/N$, the average magnetization $\sum_{i=1}^N c_i x_i$ is conserved, and all nodes have the same dynamical influence independently of the topological features of the network. In the more standard *node update* voter dynamics, at each step one node i (having degree d_i) is selected at random and copies the state of one of its neighbors j , also selected at random. In this case $K_{ij} = A_{ij}/d_i$, so that K_{ij} is no longer a symmetric matrix, the conserved quantity is a weighted magnetization [27] and the dynamical influence of node i is proportional to its degree d_i .

For diffusive processes, the system is driven towards a homogeneous final state with $x^* := x_i(\infty) = x_j(\infty)$ for all i and j . Although x^* takes continuous values, each realization of the voter dynamics in a finite system eventually reaches a homogeneous absorbing state with either all nodes in the state $+1$ or all in the state -1 . The influence c_i of a node weights the initial state of node i in the probability of which of the two absorbing states is reached. When all nodes are equivalent x^* is just the average of the initial values of the nodes, but otherwise x^* is given by the weighted average of the two absorbing states with the probability of reaching each of them. The value c_i has an alternative interpretation as a stationary density of a random walk [12].

The meaning of dynamical influence also manifests itself in the practical task of driving a system efficiently. In the context of the voter model, this task might be phrased in terms of the zealot problem [28]. One considers a special directed network in which a given node (the zealot) does not copy the state of any of its neighbors. The question is the efficiency of the zealot in driving all other nodes to the zealot state. To show the broad applicability of the dynamical influence concept, we address this question of driving efficiency considering the problem of phase-coupled oscillators described by the Kuramoto model [29]. Assuming all oscillators have the same intrinsic frequency ω , the phase variable x_i of oscillator i advances as

$$\dot{x}_i = \omega + \sum_{j=1}^N K_{ij} \sin(x_j - x_i) . \quad (6)$$

with a matrix K of non-negative coupling strengths. Around the synchronized state, phase differences are small. Without losing generality, we choose $\omega = 0$. By approximating each sin-term with its argument, a linear homogeneous system as in Eq. (1) is recovered.

We study a scenario with initially all oscillators i in phase $x_i(0) = 0$. An additional node a with constant

phase $x_a = \pi/2$ is added to the system and linked through an additional edge to a chosen node i . We measure the time T_i the system takes to reach the new homogeneous state with $s_i = \pi/2$ for all nodes i . The dynamical evolution of these systems is illustrated by studying the motif in the inset of Fig. 3a. The global phase $\psi(t)$ converges faster to the external forcing when the driving is applied to the nodes with higher influence, and the convergence of the different nodes depends on their relative network position in relation to the driver. In Fig. 3b, we show the results on a directed network of phase oscillators connected as the network of regions in the macaque cortex [24]. The extremely high correlation between dynamical influence and driving efficiency clearly shows that influence is an excellent proxy to identify better targets for controlling global behavior, even in non-linear dynamical systems. The extremely high predictive power of dynamical influence for driving efficiency (rank order correlation of driving efficiency with dynamical influence is 0.97, while 0.66 with degree ratio and -0.09 with betweenness) clearly shows that influence is an excellent proxy to identify better targets for controlling global behavior, even in non-linear dynamical systems.

To summarize, dynamical influence is a general centrality measure which is not solely based on topology but specifically designed for dynamical processes on complex networks. For critical epidemic spreading, dynamical influence is a good predictor of spreading capabilities. For diffusion, dynamical influence quantifies the impact of the dynamical states of single nodes on the asymptotic homogeneous state, and beyond that, it proves to be a high-quality proxy for driving efficiency, uncovering which are the best target nodes in real networks to be forced in order to drive the system towards specific states. In a broader context, the identification of these targets has fundamental implications and practical applications on strategies with an interest in controlling collective behavior, from social influence to biomedical responses.

METHODS

Centrality measures

The degree d_i of node i is the number of nodes i is connected to. In directed networks, in- and out-degree d_i^{in} and d_i^{out} are distinguished. For the matrix averaging over all adjacency matrices of networks with fixed node degrees, $c_i = d_i$ is a left eigenvector for the largest eigenvalue. Likewise, the degree ratios $d_i^{\text{out}}/d_i^{\text{in}}$ form a left eigenvector of the Laplacian matrix averaging over all networks with given node degrees [30, 31].

The betweenness centrality b_i of a node i quantifies the fraction of shortest paths that pass through this node [7].

It is defined as

$$b_i = \sum_{(j,k)} \frac{\sigma_{jk}(i)}{\sigma_{jk}}, \quad (7)$$

where the summation runs over all ordered node pairs (j, k) ; σ_{jk} denotes the total number of shortest paths from node j to node k ; $\sigma_{jk}(i)$ is the number of such paths running through node i .

The shell index k_i [10, 32, 33] of a node i is derived from the consideration of the k -core [33] for integer $k \geq 0$. The k -core of a network is the largest induced subnetwork in which all nodes have degree at least k . Starting from the full network, the k -core is obtained by deleting nodes (together with their edges) with degree strictly less than k until no such nodes are left. The shell-index k_i is the largest value k such that node i is contained in the k -core. In case of directed network, the k -core is based on the out-degree.

Epidemic models

We simulate the *SIR model* of epidemic spreading in the time-discrete version. Transitions between the three states (S,I,R) are as follows. If node i is in the S (susceptible) state and has ν infected (I) neighbors at time t , then node i remains susceptible with probability $(1-\beta)^\nu$, otherwise i is infected at time $t+1$. If node i is in the infected state at time t then i is in the R (removed) state at time $t+1$. In the *SIS model*, at difference with SIR, a node infected at time t is susceptible again at time $t+1$. The probability of being removed in the *SIR model* does not enter in the linearized Equation (4) because it appears only in a second order term in the equation for x . Therefore Equation (4) gives the same linear description for the *SIR* and *SIS* models.

The system is in an absorbing configuration if none of the nodes is infected. For both models, outbreak size is the number of nodes having been infected at least once before reaching an absorbing configuration. The spreading efficiency of node i is the average outbreak size when initiating the dynamics with node i infected and all others susceptible.

Rank order correlation

For a vector $x \in \mathbb{R}^n$, the rank of component i is given by

$$r_i(x) = 1 + |\{j \neq i | x_j > x_i\}| + \frac{1}{2} |\{j \neq i | x_j = x_i\}| \quad (8)$$

The rank order correlation coefficient $\rho(x, y)$ between two such vectors x and y is the Pearson correlation coefficient between the rank vectors $r(x)$ and $r(y)$. Thus $\rho(x, y)$ takes values in $[-1, 1]$ with $\rho(x, y) = +1$ (-1) if and only if x and y are in a strictly increasing (decreasing) relation.

ACKNOWLEDGMENTS

K.K. acknowledges financial support from VolkswagenStiftung and from European Commission NEST Pathfinder initiative on Complexity through project SYNLET (Contract 043312). M.A.S. acknowledges financial support by the Ramón y Cajal program of the Spanish Ministry of Science, MICINN Project No. BFU2010-21847-C02-02, and Generalitat de Catalunya grant No. 2009SGR1055. V.M.E. and M.S.M. acknowledge financial support from MEC (Spain) through project FISICOS (FIS2007-60327).

-
- [1] S. N. Dorogovtsev and J. F. F. Mendes, *Evolution of networks: From biological nets to the Internet and WWW* (Oxford University Press, Oxford, 2003).
 - [2] R. Albert and A.-L. Barabási, *Rev. Mod. Phys.* **74**, 47 (2002).
 - [3] R. Pastor-Satorras and A. Vespignani, *Physical Review Letters* **86**, 32003203 (2001).
 - [4] A.-L. Barabási and R. Albert, *Science* **286**, 509 (1999).
 - [5] H. Jeong, S. P. Mason, A.-L. Barabási, and Z. N. Oltvai, *Nature* **411**, 41 (2001).
 - [6] S. Wuchty and P. F. Stadler, *Journal of Theoretical Biology* **223**, 45 (2003).
 - [7] L. Freeman, *Sociometry* **40**, 35 (1977).
 - [8] P. Bonacich, *Journal of Mathematical Sociology* **2**, 113 (1972).
 - [9] B. Bollobás, *Graph Theory and Combinatorics: Proceedings of the Cambridge Combinatorial Conference in Honor of P. Erdős Vol. 35* (Academic, 1984).
 - [10] M. Kitsak, L. K. Gallos, F. Liljeros, L. Muchnik, H. E. Stanley, and H. A. Makse, *Nature Physics* **6**, 888893 (2010).
 - [11] N. Masuda, Y. Kawamura, and H. Kori, *New Journal of Physics* **11**, 113002 (2009).
 - [12] N. Masuda and H. Kori, *Phys. Rev. E* **82**, 056107 (2010).
 - [13] B. Golub and M. O. Jackson, *American Economic Journal: Microeconomics* **2**, 112 (2010).
 - [14] S. Brin and L. Page, *Proceedings of the Seventh International World Wide Web Conference, Computer Networks and ISDN Systems* **30**, 107 (1998).
 - [15] S. N. Dorogovtsev, A. V. Goltsev, and J. F. F. Mendes, *Rev. Mod. Phys.* **80**, 1275 (2008).
 - [16] J. D. Murray (2004).
 - [17] W. W. Zachary, *Journal of Anthropological Research* **33**, 452 (1977).
 - [18] M. Girvan and M. E. J. Newman, *Proceedings of the National Academy of Sciences of the USA* **99**, 7821 (2002).
 - [19] R. Guimerà, L. Danon, A. Díaz-Guilera, F. Giralt, and A. Arenas, *Phys. Rev. E* **68**, 065103 (2003).

- [20] D. J. Watts and S. H. Strogatz, *Nature* **393**, 440 (1998).
- [21] J. G. White, E. Southgate, J. N. Thomson, and S. Brenner, *Philosophical Transactions of the Royal Society of London. B, Biological Sciences* **314**, 1 (1986).
- [22] R. Parshani, S. Carmi, and S. Havlin, *Phys. Rev. Lett.* **104**, 258701 (2010).
- [23] T. E. Harris, *Ann. Probab.* **2**, 969 (1974).
- [24] C. J. Honey, R. Köttler, M. Breakspear, and O. Sporns, *Proceedings of the National Academy of Sciences of the USA* **104**, 10240 (2007).
- [25] R. Agaev and P. Chebotarev, *Linear Algebra and its Applications* **399**, 157 (2005), special Issue devoted to papers presented at the International Meeting on Matrix Analysis and Applications, Ft. Lauderdale, FL, 14-16 December 2003.
- [26] R. Holley and T. Liggett, *Annals of Probability* **3**, 643 (1975).
- [27] K. Suchecki, V. M. Eguíluz, and M. San Miguel, *Europhysics Letters* **69**, 228 (2005).
- [28] M. Mobilia, *Phys. Rev. Lett.* **91**, 028701 (2003).
- [29] J. A. Acebrón, L. L. Bonilla, C. J. Pérez Vicente, F. Ritort, and R. Spigler, *Reviews of Modern Physics* **77**, 137 (2005).
- [30] M. A. Serrano, K. Klemm, F. Vazquez, V. M. Eguíluz, and M. San Miguel, *Journal of Statistical Mechanics: Theory and Experiment* **2009**, P10024 (2009).
- [31] N. Masuda and H. Ohtsuki, *New Journal of Physics* **11**, 033012 (2009).
- [32] S. B. Seidman, *Social Networks* **5**, 269 (1983).
- [33] S. N. Dorogovtsev, A. V. Goltsev, and J. F. F. Mendes, *Phys. Rev. Lett.* **96**, 040601 (2006).